

SPECIFICATIONS

HOUSING - Heavy gauge extruded aluminum (material of corrosion resistant alloy.) Aluminum end plate.



ELECTRICAL - MR-16, remote transformer required, sold separately.

SOCKET - Precision die formed aluminum socket plate. G-4/G-6 with 250°C 600v Teflon coated lead wires.

MOUNTING - Recessed with flange.

APPLICATIONS

Medium profile, recessed in plenum, intended to highlight surface texture in brick, stone, stucco, tile, textured paint, fabric and wood panels.



LABELS - UL, C-UL - Dry Location.

LAMP - MR-16, 12v (narrow spot recommended) - by others.

LENS - Supertex borosilicate glass cemented in frame. Others available consult factory.

FRAME - Attached to housing via screws, removable for relamping.

FINISH - Black anodized housing, flange to be field painted.

ORDERING INFORMATION

FIXTURE	LAMP	LAMP SPACING	LENGTH	FINISH
#802ELEV				
Recessed linear elevator wall grazing system	20MR-16 = 12v, 20w 37MR-16 = 12v, 37w (maximum 74w per foot)	4 = 4" 6 = 6" 8 = 8"	specify exact length	WHT = White BLK = Black XXXX = RAL # CST = Custom (must supply chip)



**SPECIALTY LIGHTING
INDUSTRIES, INC.**

www. specialtylightingindustries.com

1306 DORIS AVENUE, OCEAN, NJ 07712 USA

800.462.7812

732.517.0800

FAX 732.517.0971