

TYPE: _____

JOB: _____

SPECIFICATIONS

HOUSING - Precision die-formed, heavy gauge, c.r.s. Welded end plates, no visible seam.

SOCKET - PAR, medium base, porcelain, 500w, 250v.

MOUNTING - Recessed, for millwork ceiling.

LABELS - UL, C-UL -Dry Location.

LAMP - PAR 30, 120v (spot recommended) - by others.




LENS - Supertex borosilicate glass. Others available consult factory.

HOUSING FINISH - Black powder paint on all recessed surfaces.

BAFFLE FINISH - RAL colors standard, consult factory for custom finishes.

APPLICATIONS

Large profile, recessed, designed to graze down walls and other flat surfaces by positioning the trim of the fixture housing near the surface to be illuminated.



ORDERING INFORMATION

FIXTURE	LAMP CENTERS	LENGTH	BAFFLE FINISH
#811-PAR30 WD			
Recessed linear wall grazing system	9 = 9" 12 = 12"	specify exact length	WHT = White BLK = Black XXXX = RAL # CST = Custom (must supply chip)



SPECIALTY LIGHTING
INDUSTRIES, INC.

www.specialtylightingindustries.com

1306 DORIS AVENUE, OCEAN, NJ 07712 USA

800.462.7812 732.517.0800 FAX 732.517.0971